
PA2400 AIRPHX®





Product Information

Description: Using a proprietary non-thermal plasma technology, AIRPHX units disinfect air drawn through the device. The oxidizing

molecules that exit the device then disinfect air and surfaces in the treatment area.

Features

Timer: 7-day programmable timer

Filters: Intake filters, require no tools to replace

Maintenance: Check filters monthly and change as needed;

replace non-thermal plasma chamber annually

Mounting Hardware: Hardware for drywall mounting included

Power Cord: Pre-installed grounded 3-prong plug; 8 ft

Estimated Equipment

Set-Up Time: 60 minutes

Tech Specs

Nominal Power (W): 60 W

Nominal Power (V): 120 VAC

Nominal Power (A): 0.5 A

Energy Consumption: 600 kw/annually

(running continuously 24/7)

Frequency: 50/60 HZ

Sound Level: <60 decibels

Actual Size: 19"H x 16"W x 9.5"D

Weight: 40 lbs

Shipping Size: 24"H x 24"W x 16"D

Shipping Weight: 47 lbs

Powerful Cleaning

Output: Oxidizing molecules, primarily gas phase H2O2

Turbine Capacity: >80 cfm

Treatment Capacity: 250,000+ cubic feet

(depending on facility layout)

Timer Configurations: ON – Unit runs based on the timer settings

OFF – Unit runs continuously

Warranty

Parts: 1 year Labor: 1 year

Maintenance Plans Available