



MSRP = \$2,995

Product Information

Description: Using a proprietary non-thermal plasma technology, AIRPHX units disinfect air drawn through the device. The oxidizing

molecules that exit the device then disinfect air and surfaces in the treatment area.

Features

Timer: 7-day programmable timer

Filters: Inexpensive foam filters, require no tools to

replace

Maintenance: Clean/change foam filters quarterly;

replace non-thermal plasma cell annually

(recommended)

Mounting Hardware: Hardware for drywall mounting included

Power Cord: Pre-installed grounded 3-prong plug; 8 ft

Estimated Equipment

Set-Up Time: 30 minutes

Tech Specs

Nominal Power (W): 48 W

Nominal Power (V): 120 VAC

Nominal Power (A): 0.5 A

Energy Consumption: 600 kw/annually

(running continuously 24/7)

Frequency: 50/60 HZ

Sound Level: <50 decibels

Actual Size: 11"H x 16"W x 5.5"D

Weight: 9 lbs

Shipping Size: 13.5"H x 20"W x 7.5"D

Shipping Weight: 11 lbs
Shipping Cost: \$49

Powerful Cleaning

Output: Gas Phase H2O2

Turbine Capacity: 40 cfm

Treatment Capacity: 50,000 – 75,000 cubic feet

(depending on facility layout)

Timer Configurations: ON – Unit runs based on the timer settings

OFF - Unit runs continuously

Warranty

Parts: 1 year Labor: 1 year

MADE IN AMERICA